



SPECIFICATIONS	
CHUCK TYPE	YASP -200
CYLINDER DIA	205 mm
PISTON STROKE	35 mm
PISTON AREA	EXTEND 330 cm <sup>2</sup> RETRACT 306 cm <sup>2</sup>
MAX. DRAW BAR PULL	EXTEND 12,408 Kgf    RETRACT 11,505 Kgf
MAX. OPERATING PRESSURE	4.0 MPa (40.8 Kg <sub>f</sub> /cm <sup>2</sup> )
MIN. OPERATING PRESSURE	0.5 MPa ( 5 Kg <sub>f</sub> /cm <sup>2</sup> )
MAX.PERMISSIBLE SPEED	5500 rpm
WEIGHT	Kg
MOMENT OF INERTIA(GD <sup>2</sup> )	Kg .m <sup>2</sup>
TATAL LEAKAGE	1.0 L/min
( 1 KN = 100 kgf , 1 MPa = 10 kgf/cm <sup>2</sup> )	

SCALE	PROJECTION	ITEM NO.	YASP-200
1:1		PART NAME	CLOSED HYDRAULIC CYLINDER PROXIMITY SWITCH TYPE
<b>SEOAM</b> 서암기계공업주식회사 SEOAM MACHINERY INDUSTRY CO.,LTD.		PART NO.	2ASP20